SUSTAINABLE DEVELOPMENT GROUP

MEAN WELL

Smart Building Power Solutions

KNX®

Wifi

Cloud/IoT

IP Network

KNX-40E-1280
1280mA
Bus Power Supply

KSR-01IP
IP Router

KNX Bus

Main Line

KNX-20E-640
640mA
Bus Power Supply

KSC-01L
Line Coupler



Sub Line

KSI-01U
USB Interface

ETS

KAA-8R-S
8 Fold Switching Actuator

Logic

KAA-4R4V-S
4 Fold Switching Dimming Actuator

0-10V

LCM-25KN **LCM-40KN** **LCM-60KN**
25W/40W/60W LED Driver

CC

PWM-60KN **PWM-120KN** **PWM-200KN**
60W/120W/200W PWM Output LED Driver

CV PWM

XLC-25KN **XLC-40KN** **XLC-60KN**
25W/40W/60W LED Driver

CC

DLC-02-KN
DALI-2 Gateway

DALI 2

- Blind/Shutter Control
- Logic — Logic Function
- Lighting Control
- Heating Control
- Push Button Interface
- CC — Constant Current Driving Mode
- CV — Constant Voltage Driving Mode
- 0-10V — DC 0-10V Dimming Control
- PWM — PWM Style Output Mode
- Data Secure

We invite you to explore

MEAN WELL

Virtual Expo

www.meanwell.com