



Test Report : IOB-05-24

5W AC-DC Industrial On Board Type Power Module

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

Other test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	150 mVp-p (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	56 mVp-p	P
2	VOLTAGE TOLERANCE	-5% ~ +5%	I/P:85VAC~305VAC O/P:FULL~MIN. LOAD Ta:25°C	+1.89%	P
3	LINE REGULATION	-1.5% ~ +1.5%	I/P:85VAC~305VAC O/P:FULL LOAD Ta:25°C	-0.60% ~ +0.44%	P
4	LOAD REGULATION	-3% ~ +3%	I/P:230VAC O/P:FULL ~MIN LOAD Ta:25°C	+1.52% ~ +0.44%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE RANGE	85VAC ~ 350VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	29V ~ 305V	P
2	FREQUENCY RANGE	47HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 85VAC ~ 305VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	81%	I/P:230VAC O/P:FULL LOAD Ta:25°C	81.59%	P
4	AC CURRENT	0.2 A (Typ)	I/P: 100VAC O/P:FULL LOAD Ta:25°C	0.131 A	P
5	INRUSH CURRENT	< 40A COLD START	I/P:230VAC O/P:FULL LOAD Ta:25°C	16.0 A	P
6	NO LOAD POWER CONSUMPTION	< 0.15W (Max)	I/P:230VAC O/P: NO LOAD Ta:25°C	0.1043 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	SHORT OUTPUT 1 HOUR NO DAMAGE	I/P:305VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE RESET AUTO RECOVER	P
2	OVER LOAD PROTECTION	>110%	I/P:230VAC O/P:TESTING Ta:25°C	162% HICCUP MODE RESET : AUTO RECOVER	P

3	OVER VOLTAGE PROTECTION	YES	I/P:230VAC O/P:MIN LOAD Ta:25°C	PROTECTION TYPE: OUTPUT VOLTAGE CLAMP	P
---	-------------------------	-----	---------------------------------------	---	---

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:3000 VAC/min	I/P-O/P:3000 VAC/min Ta:25°C	I/P-O/P: 1.266mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT																															
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:230VAC O/P:100% LOAD Ta=25℃ 2. HI AMBIENT BURN-IN : 4HRS I/P:230VAC O/P:100% LOAD Ta=50℃ 3. HI AMBIENT BURN-IN : 4HRS I/P:230VAC O/P:50% LOAD Ta=85℃ <table><tr><th>NO</th><th>Position</th><th>1</th><th>2</th><th>3</th></tr><tr><td>1</td><td>BD1</td><td>46.8℃</td><td>74.6℃</td><td>96.4℃</td></tr><tr><td>2</td><td>U1</td><td>59.2℃</td><td>87.4℃</td><td>105.0℃</td></tr><tr><td>3</td><td>D3</td><td>57.3℃</td><td>86.6℃</td><td>103.6℃</td></tr><tr><td>4</td><td>T1 線圈</td><td>54.2℃</td><td>81.0℃</td><td>99.5℃</td></tr><tr><td>5</td><td>T1 鐵芯</td><td>54.3℃</td><td>82.1℃</td><td>99.8℃</td></tr></table>			NO	Position	1	2	3	1	BD1	46.8℃	74.6℃	96.4℃	2	U1	59.2℃	87.4℃	105.0℃	3	D3	57.3℃	86.6℃	103.6℃	4	T1 線圈	54.2℃	81.0℃	99.5℃	5	T1 鐵芯	54.3℃	82.1℃	99.8℃		P
NO	Position	1	2	3																																
1	BD1	46.8℃	74.6℃	96.4℃																																
2	U1	59.2℃	87.4℃	105.0℃																																
3	D3	57.3℃	86.6℃	103.6℃																																
4	T1 線圈	54.2℃	81.0℃	99.5℃																																
5	T1 鐵芯	54.3℃	82.1℃	99.8℃																																
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P : 230VAC O/P : 100%LOAD Ta= -20℃	TEST : OK	P																															

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-KDBK-217F NOTICES 2 PARTS COUNT TOTAL FAILURE RATE : 0.1 M.T.B.F : >10000KHRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG